


SIR-E FA



> 100 dB <
> EN54-3 APPROVED <
> 2 LEVELS OF ALARM <



CAN BE INSTALLED WITH



See Base Section on page 28

	SHALLOW	DEEP	WALL
12/24V AC/DC	✓	✓	✓
PNP 12/24V DC	✗	✗	✓
	FLUSH	DOUBLE	POLE

CERTIFICATIONS



SIR-E FA | PART NO

SIR-E FA — 90378 90377

SIR-E FA

EN54-3 approved multifunctional electronic sounder with excellent acoustic performance. Developed with a multichannel technology, the FA range allows two levels of alarm powered by 13 EN54-3 approved tones. SIR-E FA allows 12 pre-alarm tones available on the 1st channel (selectable via a dip-switch) and 1 alarm steady tone (PFEER TOXIC GAS) on the 2nd channel.

TECHNICAL SPECIFICATIONS

MULTIFUNCTION

2 levels of alarm (pre-alarm, alarm) controllable via independent electric contacts

HIGH ACOUSTIC PERFORMANCE

CHANNEL 1 | PRE-ALARM

A powerful electronic tone of up to 100 dB ideal for signaling an imminent danger of a change to the standard conditions (12 EN54-3 approved tones selectable via dip-switch)

CHANNEL 2 | ALARM

A powerful electronic tone of up to 100 dB ideal for signaling a permanent danger or change to the standard conditions (1 EN54-3 approved tone: PFEER TOXIC GAS)

MULTITONE

13 EN54-3 approved tones

VOLTAGES

Must be used with LT 12/24V base

PROTECTION GRADE

IP65, suitable for outdoor applications

OPERATING TEMPERATURE

-30/+50 °C

MECHANICAL FEATURES

Self extinguishing PC body with high impact resistance, suitable for outdoor use thanks to the IP65 protection grade

ACOUSTIC FEATURES

High performance electromagnetic buzzer

DRAWINGS, DIMENSIONS AND WEIGHTS

