

# Control & Signalling Units $\phi$ 22mm (fixing)

## Assemblies for Illuminated, Non-Illuminated type Push Buttons & Selector Switches (Type RB2-B)



RB2-BZ10

Body assemblies with fixing collar & contact blocks (screw clamp terminal connections)

Description	Contact	Type	Reference
FOR PUSHBUTTONS, SELECTOR AND KEY SWITCHES	NO	STANDARD	RB2-BZ101
	NC	STANDARD	RB2-BZ102
	NO+NO	STANDARD	RB2-BZ103
	NC+NC	STANDARD	RB2-BZ104
	NO+NC	STANDARD	RB2-BZ105
	NO	GOLD FLASH	RB2-BZ1016
	NC	GOLD FLASH	RB2-BZ1026
	NO+NO	GOLD FLASH	RB2-BZ1036
	NC+NC	GOLD FLASH	RB2-BZ1046
	NO+NC	GOLD FLASH	RB2-BZ1056



RB2-BE10

Additional / replacement Contact Blocks

Description	Contact	Type	Reference
FOR MAKING UP BODY ASSEMBLIES WITH 3, 4, 5 OR MAXIMUM OF 6 CONTACT BLOCKS OR REPLACING 1 <sup>st</sup> OR 2 <sup>nd</sup> CONTACT	NO	STANDARD	RB2-BE101
	NC	STANDARD	RB2-BE102
	NO	GOLD FLASH	RB2-BE1016
	NC	GOLD FLASH	RB2-BE1026

Body assemblies for illuminated Push Buttons & Selectors with or w/o Contacts



RB2-BW06



RB2-BWL7

Description	Supply Voltage	Contact	Colour	Reference
DIRECT BA 9s FILAMENT BULB* SUPPLIED	12V / 24V / 48V / 110V / 130V (AC/DC) ■ ○	NO + NC		RB2-BW065
		W/O CONTACT BLOCKS		RB2-BW06
THROUGH RESISTOR BA 9s, 130V FILAMENT BULB SUPPLIED	220V (AC/DC)	NO + NC		RB2-BW075
		W/O CONTACT BLOCKS		RB2-BW07
THROUGH RESISTOR & DIODE BA 9s 130V BULB SUPPLIED	240V (AC)	NO + NC		RB2-BWD075
		W/O CONTACT BLOCKS		RB2-BWD07
DIRECT BA 9s NEON BULB SUPPLIED	220V / 380V / 415V (AC/DC) ■	NO + NC	●	RB2-BWN0635
			●	RB2-BWN0645
			●	RB2-BWN0655
		W/O CONTACT BLOCKS	●	RB2-BWN063
			●	RB2-BWN064
			●	RB2-BWN065
WITH INTEGRAL CIRCUIT & CLUSTER LED	12V, 24V 48V, 110V (AC / DC) 240V (AC) ■ 220V (DC)	NO + NC	●	RB2-BWL735
			●	RB2-BWL745
			●	RB2-BWL755
			●	RB2-BWL765
		W/O CONTACT BLOCKS	●	RB2-BWL73
			●	RB2-BWL74
			●	RB2-BWL75
			●	RB2-BWL76
VIA INTEGRAL TRANSFORMER 1.2 VA BA 9s, 6V FILAMENT BULB SUPPLIED	110V > 6V (AC)	NO + NC		RB2-BW035
		W/O CONTACT		RB2-BW03
FILAMENT BULB SUPPLIED	220V / 240V > 6V (AC)	NO + NC		RB2-BW045
		W/O CONTACT		RB2-BW04

- ○ Body assemblies (suitable for bulb 2.6W max.) upto 230V max. available without bulb
- \* Bulb rating 12V to 130V, 2.6W (max.)
- ■ Please mention voltage while ordering
- For accessories refer page 7, 8
- For complete assemblies refer page 9 & 10